PURCHASE ORDER

SIOUX INTERNATIONAL
6401 W 12 ST
Sioux Falls SD 57106-0244
Phone 605.336.1933 Fax 605.336.1945

DATE: 10-Feb-2016

Sold To:
Customer CITY OF HARRISBURG
Address 301 E WILLOW ST
City, State ZIP HARRISBURG SD 57032
Phone (605) 743-5872

Ship To (if different than Sold To):
Customer
Address
City, State ZIP

SALESPERSON	PO NUMBER	SHIP DATE	SHIP VIA		TERMS
RW2					Due on receipt

UNIT CODE	YEAR	MAKE, MODEL DESCRIPTION	SERIAL NO.	AMOUNT
New		BUSH HOG TD1500 15' TRI DECK FINISH MOWER		$ 12,490.00
			SHIPPING & HANDLING	

CASH PRICE	$ 12,490.00
TRADE DOWN PAYMENT	$ -
	$ 12,490.00
TAX RATE	0.00%
SALES TAX	$ -
OTHER FEES	$ -
CASH DOWN PAYMENT	$ -
TOTAL	$ 12,490.00

TRADE-IN EQUIPMENT

YEAR	MAKE, MODEL DESCRIPTION	SERIAL NO.	TRADE ALLOWANCE
			$ -

Purchaser hereby bargains, sells and conveys unto Seller the above described trade-in Equipment and warrants and certifies it to be free and clear of liens, encumbrance, and security interests, except to the extent shown below.

TRADE ALLOWANCE	$ -
LESS AMOUNT OWED TO	
NET TRADE ALLOWANCE	$ -
OTHER (Specify)	
TRADE DOWN PAYMENT	$ -

Safety Equipment Checked / Installed

By initialing the box below the purchaser is acknowledging the item purchased was equipped with the necessary safety equipment, including but not limited to items such as PTO shield, guards, operator's manual, warning and safety decals, ROPS, for the safe operation of the item by the purchaser.

☐ PURCHASER'S INITIALS

SELLER AND MANUFACTURER MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED (INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS)

NOTICE TO PURCHASER

1. Read this Contract before you sign it.
2. You are entitled to an exact and completely filled in copy of this Contract when you sign it. Keep it to protect your legal rights.
3. Purchaser acknowledges receipt of a fully completed copy of this contract and Purchaser waives notice of the acceptance or rejection of this order by the seller.

ACCEPTED BY _____ 10-Feb-16
DATE

PURCHASER'S SIGNATURE _____ 10-Feb-16
CITY OF HARRISBURG DATE

BUSH HOG®

Performance You Can Count On™

FINISHING MOWERS & TRI-DECKS

ATH SERIES

AIR TUNNEL FINISHING MOWER

IMPECCABLE GROOMING.

If a beautiful, smooth, contoured appearance is important, you want Bush Hog®. Our finishing mowers are ideal for contractors, government entities, lawncare professionals, contractors, property owners, and homeowners with large lawns. Everything about these machines is designed for performance. Floating A-frames, hitch arms, and clevis hitch follow ground contours and provide extra protection from obstacles. Offset wheels prevent tracking and soil compaction. Three overlapping blades produce a smooth, yard-like finish. Available in widths up to 90-inches, these mowers are built for low maintenance and years of trouble-free performance.

BUSH HOG® Is Built TOUGH For Better Performance And Durability

TOUGH Bush Hog® Gearboxes with tapered roller bearings provide longer life and greater protection in tough mowing conditions. Gearboxes are built to exacting Bush Hog standards.

TOUGH A-Frames float from two different positions to follow ground contours and provide extra protection when riding over obstacles. Lower hitch arms float where they are attached to the frame and the clevis hitch floats where the tractor top link attaches.

TOUGH Axle Arms built for long life are equipped with offset wheels designed to prevent tracking and reduce soil compaction.

TOUGH Field Proven Spindle Assemblies provide years of maintenance-free service. Grease fittings are easily serviced through convenient openings in the shields.

TOUGH Aramid Cord Reinforced Belts with proven Bush Hog® design deliver better performance with less maintenance than competitive machines by using only one belt.

TOUGH Fabricated Decks deliver greater strength and rigidity in tough mowing conditions. The 7-gauge decks resist wear from air flow and sand that shortens life of standard decks. Leading edge is formed at a 90 degree angle to resist bending.

TOUGH Genuine Bush Hog® Blades are heat treated uplift blades that deliver a smooth cut and long life even in sandy conditions.

SPECIFICATIONS	
MODEL	**ATH-900**
Cutting Width	90-inches
Cutting Height (1/2 inch increments)	1 to 6-inches
Tractor HP Range	35 - 55 PTO
Type Hitch	Category I
Size Blades	1/4 x 3 x 31 1/2-inches
Number of Blades	3
Blade Tip Speed	15,621 FPM
Blade Overlap	2 1/4-inches
Blade Uplift	Parallel
Driveline Size	ASAE Cat. 3
Front Roller Size (optional)	3 x 13-inches
Discharge	Right side
Deck Plate	7-gauge
Tire Size	13 x 5-inches
	(solid tire)
Belt	"C" size Aramid Cord
Gearbox	55 HP
Tractor PTO Speed	540 RPM
Belt Adjustment	Spring Loaded Idler
Approx. Weight	1164-lbs.
Options	Front Roller
Warranty	1-year limited warranty with a 5-year gearbox limited warranty

Create a manicured appearance even in thick, damp conditions

- 90-inch cutting width
- For 35 to 55 HP tractors
- Designed for thick and damp conditions
- Curved left front deck edge with tight center baffle directs material into tunnel
- Tunnel easily accommodates large volume of clippings
- Parallel uplift blades lift grass for cleaner cut
- 7-gauge steel deck
- Deck reinforcement at each spindle assembly
- High blade tip speeds (15,621 FPM) force air and material into and through tunnel
- Blades overlap for quality appearance
- Spring-loaded idler is easy to adjust
- Easy cutting height adjustment from 1 to 6-inches in ½-inch increments
- Easy-lift tabs for quick lubrication of blade spindles

RDTH SERIES

REAR DISCHARGE FINISHING MOWER

A CUT ABOVE THE REST.

Available in cutting widths of 60, 72, and 84-inches, the RDTH Series is designed to deliver a smooth, even cut with the superior distribution of rear discharge. Floating top and lower links allow for a uniform cut on uneven terrain and high blade tip speeds prevent streaking. Cutting height is easily adjustable from 1 to 6-inches. The closed box design and heavy rear discharge chain shielding reduces potential damage from thrown rocks and other debris.

Smooth, even cut with the superior distribution of rear discharge

- **TOUGH** 60 to 84-inch cutting widths
- **TOUGH** for 15 to 55+ HP tractors
- **TOUGH** designed to deliver the quality distribution of rear discharge
- **TOUGH** floating top and lower links for uniform cut on uneven terrain
- **TOUGH** high (18,000 plus FPM) blade tip speed prevents streaking
- **TOUGH** Bush Hog® field proven spindles
- **TOUGH** Single Aramid Cord reinforced belt
- **TOUGH** easy-to-use grease zerk in caster stem
- **TOUGH** spring-loaded idler adjusts belt tension
- **TOUGH** rear chains standard on RDTH-60 and RDTH-72
- **TOUGH** flared deck design on RDTH-84
- **TOUGH** easy cutting height adjustment from 1 to 6-inches
- **TOUGH** 7-gauge steel deck

SPECIFICATIONS			
MODEL	**RDTH-60**	**RDTH-72**	**RDTH-84**
Cutting Width	60-inches	72-inches	84-inches
Cutting Height (1/2 inch increments)	1 1/2 to 6 1/2-inches	1 1/2 to 6 1/2-inches	1 1/2 to 5 1/2-inches
Tractor HP Range	15 - 35 PTO	20 - 40 PTO	30 - 55 PTO
Type Hitch	Category I	Category I	Category I
Size Blades	1/4 x 2.5 x 21-inches	1/4 x 2.5 x 25-inches	5/16 x 2.5 x 29-inches
Number of Blades	3	3	3
Blade Tip Speed	18,231 FPM	18,272 FPM	18,475 FPM
Blade Overlap	1 1/2-inches	1 1/2-inches	1 1/2-inches
Blade Uplift	Parallel	Parallel	Parallel
Driveline Size	ASAE Category 3	ASAE Category 3	ASAE Category 3
Front Roller Size (optional)	3 x 5-inches	3 x 5-inches	3 x 13-inches
Discharge	Rear	Rear	Rear
Deck Plate	7-gauge	7-gauge	7-gauge
Tire Size	3 1/4 x 10 1/4-inches	3 1/4 x 10 1/4-inches	4 x 10-inches
	(solid tire)	(solid tire)	(solid tire)
Belt	“B” size Aramid Cord	“B” size Aramid Cord	“B” size Aramid Cord
Gearbox	45 HP	45 HP	55 HP
Tractor PTO Speed	540 RPM	540 RPM	540 RPM
Belt Adjustment	Spring Loaded Idler	Spring Loaded Idler	Spring Loaded Idler
Approx. Weight	536-lbs.	588-lbs.	874-lbs.
Options	Front Roller Kit	Front Roller Kit	Front Roller Kit
Warranty	1-year limited warranty with a 5-year gearbox limited warranty		

TD SERIES

TRI-DECK FINISHING MOWERS

The Bush Hog® line of Tri-Deck Finishing Mowers are perfect wherever a well-groomed cut is needed. With available mowing widths of 11, 15 and 17-feet, there is certain to be a size to fit your needs. Power requirements start at only 30 HP for the TD1100 and range up to 45 HP for the TD1700. Chances are you already have a tractor that is compatible with at least one of these mowers.

The entire TD line is well suited for golf courses, municipalities, sporting complexes, and homeowers with large acreages.

The high blade tip speed and 6-inches deck overlap assures a uniform cut with no streaking. Built "Bush Hog Tough," this line is designed to withstand thousands of hours of use with minimal downtime.

With a choice of three models, the TD Series meets your expectations of quality mowers from "The Factory Where Legends Are Built."

Bush Hog® TOUGH Features

for Sod Farms, Golf Courses, Parks, Recreation Areas...

- **Streamlined** deck design
- **Reinforced** mainframe construction
- **Independent** deck flotation
- **Heavy duty** Aramid Cord belting
- **Large** transport wheels for better flotation and stability
- **Deck Gearbox** – 45 HP
- **Heavy duty** divider gearbox
- **Economical pricing**, choice of widths
- **Adjustable** clevis hitch
- **Greaseable blade spindles**
- **Standard** front anti-scalp rollers
- **Narrow** transport width

The adjustable clevis hitch, along with the standard tongue jack, allows one person to attach mower to the tractor. The safety tow chain is standard equipment.

The 3 x 5-inches anti-scalp front roller is standard equipment for all decks.

SPECIFICATIONS

	TD1100	TD1500	TD1700
Cutting Width	11-feet	15-feet	17-feet
Cutting Height	3/4-inch to 4 1/4-inches	1 1/2-inches to 4 1/2-inches	1 1/2-inches to 4 1/2-inches
Deck Widths	(3) 48-inches decks	(1) 72-inches deck, (2) 60-inches decks	(3) 72-inches decks
Deck Construction	7-gauge	7-gauge	7-gauge
Deck Overlap	6-inches	6-inches	6-inches
Blade Overlap	1 1/2-inches	1 1/2-inches	1 1/2-inches
Material Discharge	Rear	Rear	Rear
Rear Chains	Standard equipment	Standard equipment	Standard equipment
Belts	Single Aramid Cord “B” section per deck	Single Aramid Cord “B” section per deck	Single Aramid Cord “B” section per deck
Gauge Wheels	(12) 11-inches x 4-inches pneumatic w/roller bearings	(12) 13-inches x 5-inches x 6-inches pneumatic w/roller bearings	(12) 13-inches x 5-inches x 6-inches pneumatic w/roller bearings
Tractor HP Required*	30 HP minimum	40 HP minimum	45 HP minimum
Gearbox RPM	540	540	540
Spindle RPMs	4150	3316 (60-inches), 2792 (72-inches)	2792
Transport Dimensions	78-inches wide, 75-inches high, 146-inches long	95-1/2-inches wide, 95-1/2-inches high, 166" long	95-1/2-inches wide, 107-1/2-inches high, 166-inches long
Trans. Tires (w/taper. roll.bearings)	(2) 23-inches x 9-1/2-inches x 12-inches	(2) 23-inches x 9-1/2-inches x 12-inches	(2) 23-inches x 9-1/2-inches x 12-inches
Wing Flex	30° up and 10° down	30° up and 10° down	30° up and 10° down
Hitch	Pull type/clevis, 3 position adjustable	Pull type/clevis, 3 position adjustable	Pull type/clevis, 3 position adjustable
Driveline Size	Cat IV 80° CV (main), Cat. III wing	Cat IV 80° CV (main), Cat. III wing	Cat IV 80° CV (main), Cat. III wing
Wing Deck Flex (ind. of wing frame)	10° side to side, 10° front to rear	10° side to side, 10° front to rear	10° side to side, 10° front to rear
Belt Adjustment	Spring loaded idler	Spring loaded idler	Spring loaded idler
Blade Tip Speed	18,468 FPM	18,231 (60-inches), 18,272 (72-inches) FPM	18,272 FPM
Parking Jack	Standard	Standard	Standard

* HORSEPOWER SUBJECT TO CHANGE DUE TO MOWING CONDITIONS SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

2501 Griffin Ave.
Selma, Alabama 36703
Tel: (800) 363-6096
Fax: (334) 874-2701

www.bushhog.com

Bush Hog and (hog icon) are registered trademarks of Alamo Group, Inc. Copyright © 2015